

bimetal stainless steel thermometer BiTh 100 E

Part no. 66349312

Bimetal stainless steel thermometers

benefits

- suitable for use in mechanical engineering, plant engineering, process engineering or food industry
- ideal for hygienic processes
- accuracy class 1 as per EN 13190
- for temperatures of the medium of up to 160 °C
- with adapter ring for thermowell Ø 18 mm

Application

For corrosive media. Suitable for a great range of industrial applications.

Technical Specifications

Type
D3

Nominal size
100

measuring element
Bimetal helix

accuracy class
1 (EN 13190)

ranges °C
0/120

Application area (EN 13190)
continuous load: Measuring range
short-term: Range

Operating pressure at thermowell
(not included in scope of delivery)
max. 25 bar

Degree of protection
IP 43 (EN 60529)

standard version

Connection
Stem: Stainless steel 316 Ti/L, ∅ 8 mm
Stem: plain

mounting position
centre back

Dial
Aluminium, white
Scaling: black

Pointer
Aluminium, black

Housing
Stainless steel 304

push on bezel
Stainless steel 304


window
Instrument glass

Options

- Thermowell G½B, stainless steel 316 Ti/316 L
- other connection designs
- other ranges
- other stem lengths

Technical Drawings

centre back connection, plain



Dimensions (mm)

NG	b1	D	l2
63	15	63	67
63	15	63	104
63	15	63	154
63	15	63	204
80	15	80	67
80	15	80	104
80	15	80	154
80	15	80	204
100	17	100	67
100	17	100	104
100	17	100	154
100	17	100	204

Versions

	Type	housing ⌀	mounting position	Connection	Range	For thermowell with length L1	Stem length L1	Type	Type		Part no.
	BiTh 100 E	100 mm	centre back	plain	0/120 °C	150 mm		BiTh 100 E	D312	●	66349312

● in-stock items

○ Non-stock items