




## Bimetal stainless steel thermometers

### benefits

- suitable for use in mechanical engineering, plant engineering, process engineering or food industry
- ideal for hygienic processes
- accuracy class 1 as per EN 13190
- for temperatures of the medium of up to 160 °C
- with adapter ring for thermowell Ø 18 mm

## Application

For corrosive media. Suitable for a great range of industrial applications.

## Technical Specifications

### Type

D3

### Nominal size

80

### measuring element

Bimetal helix

### accuracy class

1 (EN 13190)

### ranges °C

0/60

### Application area (EN 13190)

continuous load: Measuring range  
short-term: Range

### Operating pressure at thermowell

(not included in scope of delivery)  
max. 25 bar

### Degree of protection

IP 43 (EN 60529)

## Options

- Thermowell G $\frac{1}{2}$ B, stainless steel 316 Ti/316 L
- other connection designs
- other ranges

### Connection

Stem: Stainless steel 316 Ti/L, Ø 8 mm  
Stem: fixed male connection, fixed G $\frac{1}{2}$ B

### mounting position

centre back

### Dial

Aluminium, white  
Scaling: black

### Pointer

Aluminium, black

### Housing

Stainless steel 304

### push on bezel

Stainless steel 304


### window

Instrument glass

- other stem lengths

## Technical Drawings

centre back connection, fixed male connection



Dimensions (mm)

| NG  | D   | b1 | b5 | l1  | G   |
|-----|-----|----|----|-----|-----|
| 63  | 63  | 15 | 27 | 63  | G½B |
| 63  | 63  | 15 | 27 | 80  | G½B |
| 63  | 63  | 15 | 27 | 100 | G½B |
| 80  | 80  | 15 | 28 | 63  | G½B |
| 80  | 80  | 15 | 28 | 80  | G½B |
| 80  | 80  | 15 | 28 | 100 | G½B |
| 100 | 100 | 17 | 29 | 63  | G½B |
| 100 | 100 | 17 | 29 | 80  | G½B |
| 100 | 100 | 17 | 29 | 100 | G½B |

Versions

| Type         | housing<br>ø | moun-<br>ting po-<br>sition | Connec-<br>tion                                    | Range   | For ther-<br>mowell<br>with<br>length<br>L1 | Stem<br>length<br>L1 | Type         | Type | Part no.                                                                                                  |
|--------------|--------------|-----------------------------|----------------------------------------------------|---------|---------------------------------------------|----------------------|--------------|------|-----------------------------------------------------------------------------------------------------------|
| BiTh 80<br>E | 80 mm        | centre<br>back              | fixed<br>male<br>connec-<br>tion,<br>fixed<br>G1½B | 0/60 °C |                                             | 63 mm                | BiTh 80<br>E | D312 |  66232312AF-<br>G4D8   |
| BiTh 80<br>E | 80 mm        | centre<br>back              | fixed<br>male<br>connec-<br>tion,<br>fixed<br>G1½B | 0/60 °C |                                             | 100 mm               | BiTh 80<br>E | D312 |  66233312AF-<br>G4D8   |
| BiTh 80<br>E | 80 mm        | centre<br>back              | fixed<br>male<br>connec-<br>tion,<br>fixed<br>G1½B | 0/60 °C |                                             | 150 mm               | BiTh 80<br>E | D312 |  66234312AF-<br>G4D8   |
| BiTh 80<br>E | 80 mm        | centre<br>back              | fixed<br>male<br>connec-<br>tion,<br>fixed<br>G1½B | 0/60 °C |                                             | 200 mm               | BiTh 80<br>E | D312 |  66235312AF-<br>G4D8 |

-  in-stock items
-  Non-stock items