



## bimetal standard thermometer BiTh 80 K

**Part no. 63779**

**Bimetal thermometer with brass thermowell**

### benefits

- ranges: -20/+60, 0/60, 0/120, 0/160 °C
- thermowell brass with optional self-sealing thread with PTFE sealing ring
- stem brass or aluminium

### Application

Heating, plumbing

### Technical Specifications

#### Nominal size

80

#### measuring element

Bimetal helix

#### accuracy class

2 (EN 13190)

### standard version

#### Connection

Stem: brass or aluminium, Ø 9 mm

Thermowell: G1/2B, Brass, Ø 12 mm, removable

#### mounting position

centre back

#### Dial

Plastic, white

Scaling: black

### Options

- nominal size 63 (bottom back)

#### ranges °C

-20/+60

#### application area

Full scale value

#### Operating pressure at thermowell

max. 6 bar

#### Pointer

Plastic, black

#### Housing


ABS, black

#### window

Plastic, clipped in

Technical Drawings

Centre back connection, NG 63 – 80 – 100



Dimensions (mm)

| NG  | B    | D   | d1 | G   | L1  | L2  | SW |
|-----|------|-----|----|-----|-----|-----|----|
| 63  | 14,7 | 62  | 12 | G½B | 40  | 61  | 19 |
| 63  | 14,7 | 62  | 12 | G½B | 63  | 85  | 19 |
| 63  | 14,7 | 62  | 12 | G½B | 100 | 122 | 19 |
| 63  | 14,7 | 62  | 12 | G½B | 150 | 172 | 19 |
| 80  | 14,8 | 79  | 12 | G½B | 40  | 61  | 19 |
| 80  | 14,8 | 79  | 12 | G½B | 63  | 85  | 19 |
| 80  | 14,8 | 79  | 12 | G½B | 100 | 122 | 19 |
| 80  | 14,8 | 79  | 12 | G½B | 150 | 172 | 19 |
| 100 | 15   | 100 | 12 | G½B | 40  | 61  | 19 |
| 100 | 15   | 100 | 12 | G½B | 63  | 85  | 19 |
| 100 | 15   | 100 | 12 | G½B | 100 | 122 | 19 |
| 100 | 15   | 100 | 12 | G½B | 150 | 172 | 19 |
| 100 | 15   | 100 | 12 | G½B | 200 | 222 | 19 |

Versions

| Type      | housing ø | Conne-<br>ction | mounting<br>position | Range         | Stem<br>length | Stem<br>length | Type      | Part no. |
|-----------|-----------|-----------------|----------------------|---------------|----------------|----------------|-----------|----------|
| BiTh 80 K | 80 mm     | Thermo-<br>well | centre<br>back       | -20/+60<br>°C | 150 mm         |                | BiTh 80 K | 63779    |

-  in-stock items
-  Non-stock items