



Bourdon tube pressure gauge for chemical applications type D7 with glycerine filling

housing ø (nominal size)	63 mm
Connection	G $\frac{1}{4}$ B
alignment	bottom
accuracy class	1.6
standard	EN 837-1

benefits

- for chemical and process engineering applications
- measuring system fully welded to housing
- extremely robust design
- can be used in case of heavy vibrations and high, dynamic pressure loads
- tightness-tested with helium
- DNV- and GOSSTANDART-certified
- Ex version (optional)

Application

For corrosive gaseous and liquid media which are not highly viscous and do not crystallise; suitable for corrosive environments. For measurements in areas with high vibration levels and high, dynamic pressure loads.

! For measuring gas or vapour, observe the table "Selection Criteria as per EN 837-2" (see appendix)!

Technical Specifications

Type
D7

Nominal size
63

accuracy class (EN 837-1/6)
1.6

ranges (EN 837-1/5)
see ordering table

application area
static load: $\frac{3}{4}$ x full scale value
dynamic load: $\frac{2}{3}$ x full scale value
short-term: Full scale value

Operating temperature range
Medium: max. 100 °C
Ambient: -20/+60 °C

Temperature performance

Indication error when the temperature of the measuring system deviates from the normal temperature of 20 °C:
at rising temperature approx. ± 0.4 %/10 K
falling temperature approx. ± 0.4 %/10 K
of full scale value

Connection

Stainless steel 316 L, bottom

Measuring element

Bourdon tube, stainless steel 316 Ti/316 L
 ≤ 60 bar: "C" type tube
> 60 bar: helical tube
tightness-tested with helium

movement

Stainless steel

Dial

Aluminium, white
Scaling: black

Pointer

Aluminium, black

Housing

Stainless steel 304, with blow-out

bayonet bezel

NG 63

Options

- Filling liquid silicone oil
- plastic window (NG 63)
- Back flange (NG 63)
- clamp fixing
- Ex version
- Crimped bezel, polished
- special scales
- other process connections

crimped bezel

Stainless steel 304

window


NG 63
Laminated safety glass

filling liquid

glycerine (99.5 %)

Technical Drawings

NG 50/63 – bottom connection



Dimensions (mm)

NG	a	b	Øc	c1	c2	D	G	h	s	SW
50	10,5	28	5	2	13	53	G1/4B	46	4,5	14
63	11,5	32	5	2	13	68	G1/4B	53	7	14

Versions

Range	Mounting type	Type		Part number
-1/+0 bar	direct	RF63ChGly D702		85101702
-1/+0.6 bar	direct	RF63ChGly D702		85102702
-1/+1.5 bar	direct	RF63ChGly D702		85103702
-1/+3 bar	direct	RF63ChGly D702		85104702
-1/+5 bar	direct	RF63ChGly D702		85105702
-1/+9 bar	direct	RF63ChGly D702		85106702
-1/+15 bar	direct	RF63ChGly D702		85107702
0/0.6 bar	direct	RF63ChGly D702		85109702
0/1 bar	direct	RF63ChGly D702		85110702
0/1.6 bar	direct	RF63ChGly D702		85111702
0/2.5 bar	direct	RF63ChGly D702		85112702
0/4 bar	direct	RF63ChGly D702		85113702
0/6 bar	direct	RF63ChGly D702		85114702
0/10 bar	direct	RF63ChGly D702		85115702
0/16 bar	direct	RF63ChGly D702		85116702
0/25 bar	direct	RF63ChGly D702		85117702
0/40 bar	direct	RF63ChGly D702		85118702
0/60 bar	direct	RF63ChGly D702		85119702

0/100 bar	direct	RF63ChGly D702	●	85120702
0/160 bar	direct	RF63ChGly D702	●	85121702
0/250 bar	direct	RF63ChGly D702	●	85122702
0/400 bar	direct	RF63ChGly D702	●	85123702
0/600 bar	direct	RF63ChGly D702	●	85124702
0/1000 bar	direct	RF63ChGly D702	●	85125702

● in-stock items

● Non-stock items