

Bourdon tube pressure gauges Process Gauge RF130PG

Part no. 87924101

Standard Bourdon tube pressure gauge type D1

benefits

- extremely robust pressure gauge for offshore and onshore applications
- glass-fibre reinforced safety housing with solid baffle wall and blow-out
- integrated pressure compensation diaphragm
- tightness-tested with helium
- GOSSTANDART-certified

Application

For corrosive gaseous and liquid media which are not highly viscous and do not crystallise. Specially suitable for the oil and chemical industries.

Technical Specifications

Type
D1

Nominal size
4.5

accuracy class (ASME B 40.100)
Grade 2A (correspond to an accuracy of 0.5 %)

ranges (EN 837-1/5)
see ordering table

application area
static load: Full scale value
dynamic load: 0.9 x full scale value
short-term: 1.3 x full scale value

standard version

Operating temperature range
Medium: max. 100 °C
Ambient: -40/+65 °C

Temperature performance
Indication error when the temperature of the measuring system deviates from the normal temperature of 20 °C:
at rising temperature approx. ± 0.4 %/10 K
falling temperature approx. ± 0.4 %/10 K
of full scale value

Degree of protection
IP 67 (EN 60529)

Connection
Brass
D101
bottom

Measuring element
Bourdon tube, stainless steel 316 Ti/316 L
≤ 60 bar: "C" type tube
> 60 bar: helical tube
tightness-tested with helium

movement
Stainless steel

Dial
Aluminium, white
Scaling: black

Options

- Glycerine filling (type D 6)
- Silicone oil filling (type D 6)
- Measuring system copper alloy (type 1x1)
- Measuring system Monel (type 1x3)
- laminated safety glass window
- Reference pointer
- Maximum pointer
- Electrical contacts
- special scales
- other process connections

Pointer
micro-adjustable pointer
Brass, black

Housing
PP-GF20, black
with solid baffle wall and blow-out,
Integrated back flange

Screw type bezel
PP-GF20, black Internal

window
Plastic (PMMA)

Technical Drawings

Bottom connection



Dimensions (mm)

NG	a	b	c1	c2	d1	d2	d3	∅D	G	h	h1	s1	s2	SW
4½"	40	82,5	15	20	137	148	6	129	½-14 NPT	102	67	12,5	25	22

Versions

Range	Mounting type	Type		Part number
0/600 bar	back flange	RF130PG D101	●	87924101

● in-stock items

○ Non-stock items