capacitance level indicator CapFox® EFT 20 KX -41 HT

Part no. 5655041HT-L-3B01

capacitance level indicator

benefits

- easy adjustment via magnetic pin
- Degree of protection IP 68 with fixed cable connection
- for tank heights of 100 mm and more
- EX version suitable for mining

Application

Capacitance level indicator with 2-wire or 3-wire technology for continuous level measurement of liquids and bulk solids (flour, sand, cement, plastic granules) in open and closed container, tanks or silos. Particularly suitable for low tank heights.

Description

The capacitance level indicator CapFox® EFT 20 detects the change in electrical capacitance caused by the change in level and converts the amount of change into a current signal (4–20 mA) or a voltage signal (0–10 V). The electronics module is contained in a robust stainless steel housing. Flexible probes or rod probes are available as measurement electrode. For level measurement of adhesive, corrosive or electrically conductive media, the electrodes are available with an insulating coating. If media are stored in tanks made of non-conductive materials or in open containers, the probes must be equipped with an additional coax reference pipe or an earth electrode.

Technical Specifications

Indicator
LED green: Operation
LED orange: status

max. measuring range
KX
≤ 1000 mm
(specify exact probe length when ordering)

Operating temperature range
Medium: -40/+300 °C
HT version: -40/+200 °C
Ambient: -30/+85 °C

Process connection
¾" NPT

material
Housing: Stainless steel 304
KX
Stainless steel 304

Supply voltage
DC 9 – 34 V

Output signal
4–20 mA, 2-wire

Current input
max. 20.4 mA

Load
R_{max} = 700 Ω at U = 24 V

Degree of protection
IP 68 (EN 60529)

Electrical connection
Cable gland M12 x 1.5 with fixed cable connection
Cable length: 2 m

Weight
HT version
ca. 0.6 kg

Scope of delivery
- CapFox® EFT 20 according to configuration
- magnetic pin

Options

- other process connections
- FEP/PFA coatings
- Ex version
- Ex II 1 G Ex ia IIB T4 Ga
- Ex II 1/2 D Ex ia IIIC T120°C Da/Db
- Ex M1 Ex ia I Ma

Technical Drawings

Electrical connection D with dust-tight cable gland (ATEX)



Dimensions (mm)

Versions

	model / series	Process connection		Part no.
CapFox® EFT 20 KX	CapFox® EFT 20 KX -41 HT	¾" NPT	●	5655041HT-L-3B01

● in-stock items

○ Non-stock items