



## Glycerine filled Bourdon tube pressure gauges RF63Gly

Part no. 85120641

Glycerine filled Bourdon tube pressure gauge type D6

### benefits

- can be used in case of heavy vibrations and high, dynamic pressure loads
- longer service life due to less wear and corrosion protection of the measuring system
- No steaming up of the inside of the window in case of outdoor applications

### Application

For gaseous and liquid media which are not highly viscous, do not crystallise and do not attack copper alloys. For measurements in areas with high vibration levels and high, dynamic pressure loads.

### Technical Specifications

#### Type

D6

#### Nominal size

63

#### accuracy class (EN 837-1/6)

1.6

#### ranges (EN 837-1/5)

see ordering table

#### standard version

#### Connection

Brass, centre back

#### application area

static load:  $\frac{1}{4}$  x full scale value

dynamic load:  $\frac{2}{3}$  x full scale value

short-term: Full scale value

#### Operating temperature range

Medium: max. 60 °C

Ambient: -20/+60 °C

#### Degree of protection

IP 65 (EN 60529)

#### Measuring element

Bourdon tube, Copper alloy

≤ 60 bar: "C" type tube

> 60 bar: helical tube

**movement**

Brass

**Dial**

NG 63

Aluminium, white

Scaling: black

**Pointer**

NG 63

Aluminium, black

**Housing**

NG 63

Polyamide, black  
with blow-out

**crimped bezel**

NG 63

Aluminium, black

**window**

NG 63

Plastic

**filling liquid**


glycerine (99.5 %)

**Options**

- Back flange (NG 63)
- clamp fixing (NG 50/63)
- 3-hole fixing, panel mounting bezel (NG 63)
- throttle screw
- special scales
- other process connections

**Technical Drawings**

Centre back connection, with clamp fixing



Dimensions (mm)

| NG | b    | Øc | c1 | c2 | D  | G                 | g    | m  | n  | s | SW |
|----|------|----|----|----|----|-------------------|------|----|----|---|----|
| 50 | 31,5 | 5  | 2  | 13 | 53 | G $\frac{1}{4}$ B | 54,5 | 82 | 73 | 5 | 14 |
| 63 | 32   | 5  | 2  | 13 | 68 | G $\frac{1}{4}$ B | 55   | 94 | 82 | 7 | 14 |

Versions

| Range     | Mounting type | Type            |                                                                                     | Part number |
|-----------|---------------|-----------------|-------------------------------------------------------------------------------------|-------------|
| 0/100 bar | clamp fixing  | RF63Gly<br>D641 |  | 85120641    |

-  in-stock items
-  Non-stock items