



Standard Bourdon tube pressure gauge type D2

housing $\varnothing$ (nominal size)	40 mm
Connection	G $\frac{1}{8}$ B
alignment	centre back
accuracy class	1.6
standard	EN 837-1

benefits

- for pneumatic and heating system applications (NG 40 - 50 - 63)
- for domestic technology and mechanical engineering applications (NG 80 - 100 - 160)
- robust steel housing
- window with adjustable reference pointer (NG 80 - 100)
- with reference pointer on dial (NG 160)
- Accuracy class 1.6
- many customised versions available

Application

For gaseous and liquid media which are not highly viscous, do not crystallise and do not attack copper alloys.

! For measuring gas or vapour, observe the table "Selection Criteria as per EN 837-2"!

Technical Specifications

Type

D2

Nominal size

40

accuracy class (EN 837-1/6)

1.6

ranges (EN 837-1/5)

see ordering table

application area

static load: $\frac{3}{4}$ x full scale value

dynamic load: $\frac{3}{4}$ x full scale value

short-term: Full scale value

Operating temperature range

Medium: max. 60 °C

Ambient: -20/+60 °C

Temperature performance

Indication error when the temperature of the measuring system deviates from the normal temperature of 20 °C:

at rising temperature approx. ± 0.4 %/10 K

falling temperature approx. ± 0.4 %/10 K

of full scale value

Degree of protection

IP 32 (EN 60529)

Connection

Brass, centre back

Measuring element

Bourdon tube, Copper alloy

≤ 60 bar: "C" type tube

> 60 bar: helical tube

movement

Brass

Dial

NG 40

Plastic, white

D251

Scale

D251

dual scale, bar outer, black – psi inner, red

Pointer

NG 40

Housing

Sheet steel, black

push on bezel

NG 40

window

NG 40


Plastic, clipped in

Options

- Panel mounting bezel
- 3-hole fixing, panel mounting bezel
- throttle screw
- Reference pointer
- special scales
- other process connections

Technical Drawings

NG 40/50/63 – centre back connection, panel mounting bezel with clamp fixing



Dimensions (mm)

NG	b3	c2	d6	g2	G	m	s3	SW
40	28	10	44	46,6	G $\frac{1}{8}$ B	50	5,2	12
50	30,3	13	54	51,3	G $\frac{1}{4}$ B	45	5,4	14
63	30,3	13	67,8	53,3	G $\frac{1}{4}$ B	51,5	5,6	14

Versions

Range	Mounting type	Type		Part number
-1/+0 bar	Panel mounting bezel, with clamp fixing	RF40 D251	●	85001251
0/1 bar	Panel mounting bezel, with clamp fixing	RF40 D251	●	85010251
0/1.6 bar	Panel mounting bezel, with clamp fixing	RF40 D251	●	85011251
0/2.5 bar	Panel mounting bezel, with clamp fixing	RF40 D251	●	85012251
0/4 bar	Panel mounting bezel, with clamp fixing	RF40 D251	●	85013251
0/6 bar	Panel mounting bezel, with clamp fixing	RF40 D251	●	85014251
0/10 bar	Panel mounting bezel, with clamp fixing	RF40 D251	●	85015251
0/16 bar	Panel mounting bezel, with clamp fixing	RF40 D251	●	85016251
0/25 bar	Panel mounting bezel, with clamp fixing	RF40 D251	●	85017251
0/40 bar	Panel mounting bezel, with clamp fixing	RF40 D251	●	85018251
0/60 bar	Panel mounting bezel, with clamp fixing	RF40 D251	●	85019251
0/100 bar	Panel mounting bezel, with clamp fixing	RF40 D251	●	85020251
0/160 bar	Panel mounting bezel, with clamp fixing	RF40 D251	●	85021251
0/250 bar	Panel mounting bezel, with clamp fixing	RF40 D251	●	85022251

● in-stock items

● Non-stock items