# Standard Bourdon tube pressure gauges RF50

## Part no. 85062251

## Standard Bourdon tube pressure gauge type D2

**benefits**

- for pneumatic and heating system applications (NG 40 - 50 - 63)
- for domestic technology and mechanical engineering applications (NG 80 - 100 - 160)
- robust steel housing
- window with adjustable reference pointer (NG 80 - 100)
- with reference pointer on dial (NG 160)
- Accuracy class 1.6
- many customised versions available

## Application

For gaseous and liquid media which are not highly viscous, do not crystallise and do not attack copper alloys.
! For measuring gas or vapour, observe the table "Selection Criteria as per EN 837-2"!

## Technical Specifications

**Type**
D2

**Nominal size**
50

**accuracy class (EN 837-1/6)**
1.6

**ranges (EN 837-1/5)**
see ordering table

**application area**
static load: ¾ x full scale value
dynamic load: ⅔ x full scale value
short-term: Full scale value

**Operating temperature range**
Medium: max. 60 °C
Ambient: -20/+60 °C

**Temperature performance**
Indication error when the temperature of the measuring system deviates from the normal temperature of 20 °C:
at rising temperature approx. ± 0.4 %/10 K
falling temperature approx. ± 0.4 %/10 K
of full scale value

**Degree of protection**
IP 32 (EN 60529)

### standard version

**Connection**
Brass, centre back

**Measuring element**
Bourdon tube, Copper alloy
≤ 60 bar: "C" type tube
> 60 bar: helical tube

**movement**
Brass

**Dial**
NG 50
Plastic, white
D251

**Scale**
D251
dual scale, bar outer, black – psi inner, red

**Pointer**
NG 50

**Housing**
Sheet steel, black

**push on bezel**
NG 50

**window**
NG 50
Plastic, clipped in

## Options

- Panel mounting bezel
- 3-hole fixing, panel mounting bezel
- throttle screw
- Reference pointer
- special scales
- other process connections

## Technical Drawings

**NG 40/50/63 – centre back connection, panel mounting bezel with clamp fixing**




**Dimensions (mm)**

| NG | b3 | c2 | d6 | g2 | G | m | s3 | SW |
|---|---|---|---|---|---|---|---|---|
| 40 | 28 | 10 | 44 | 46,6 | G⅛B | 50 | 5,2 | 12 |
| 50 | 30,3 | 13 | 54 | 51,3 | G¼B | 45 | 5,4 | 14 |
| 63 | 30,3 | 13 | 67,8 | 53,3 | G¼B | 51,5 | 5,6 | 14 |

## Versions

| Range | Mounting type | Type | | Part number |
|---|---|---|---|---|
| 0/2.5 bar | Panel mounting bezel, with clamp fixing | RF50 D251 | ● | 85062251 |

● in-stock items

○ Non-stock items