

tank protection package AK-S

Part no. 43901.003

for fuel oil and diesel

benefits

- inner lining package for standardised cylindrical tanks (EN/DIN) with all mounting accessories and vacuum type leak detector Eurovac
- tank protection packages for rectangular and spherical tanks on request
- customised training seminars on installation of inner linings and leak detectors possible
- materials resistant to biofuel and biodiesel mixtures with max. 30 % FAME

Application

Suitable for fuel oil EL (DIN 51603-1), diesel fuel (EN 590), liquid fuels as per DIN SPEC 51603-6 and DIN/TS 51603-8 as well as biofuel and biodiesel with a maximum of 30 % FAME (EN 14214). Use with the new paraffinic fuels HVO or GTL as an admixture is also possible. It is not generally suitable for use with paraffinic fuels and engine fuels. Suitability must be assessed on a case-by-case basis. Please contact us to discuss your specific application.

Description

Tank protection package with complete accessories for standardised cylindrical tanks. Enquire for rectangular and spherical tanks.

Technical Specifications

approval

CE as per European Construction Products Regulation ((EU) No 305/2011 and No 574/2014),
EN 13160-1:2003,
EN 13160-7:2003,
DIBt: Z-65.30-162

Scope of delivery

- Leak protection lining according to standard or made to size
- Vacuum type leak detector Eurovac
- Front wall lining made of fleece LSV2
- Intermediate layer made of fleece
- Mipoplast plate 800 x 800 mm
- Condensate bar triple 4/6 mm
- Liquid barrier 4/6 mm
- Angled nipple short 4/6 mm
- Angled nipple long 4/6 mm
- PVC suction line 3 x 6 mm perforated and not perforated
- Fastening ring 500 mm or 600 mm
- Hose connector 4 or 6 mm
- T piece hose connection 4 or 6 mm
- hose connector kit ND4/6 G⅜ x G⅛
- Warning sign with holder and felt overshoes

Versions

Tank volume	Part no.
3000 l	43901.003

- in-stock items
- Non-stock items